

Docket No. 020417

Serial No. 10/765,766

**AMENDMENTS TO THE CLAIMS:**

1 (Currently Amended): A programmable clock circuit to generate frequencies from an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal, the circuit comprising:

a counter configured to receive the input clock signal and to generate a counter signal having a frequency of  $M$  cycles for every  $N$  cycles of the input clock signal;

a comparator circuit coupled to the counter to compare a count value of the counter with predetermined count values and to generate comparator signals related to the comparison; and

a control circuit to generate an output clock signal based on the comparator signals to thereby select a rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and to select a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal;

wherein the counter is a  $M/N:D$  counter where  $D$  is related to a duty cycle of the output clock signal;

wherein the control circuit generates the output clock signal with a falling edge of the output clock signal based on a rising edge of the input clock signal if the comparator signals indicate that the counter has a value greater than or equal to  $D$  and less than  $D+M/2$ .

2 (Original): The circuit of claim 1 wherein the control circuit generates the output clock signal with a rising edge of the output clock signal based on a rising edge of the input clock signal if the comparator signals indicate that the counter has a value greater than or equal to zero and less than  $M/2$ .

3 (Original): The circuit of claim 1 wherein the control circuit generates the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock signal if the comparator signals indicate that the counter has a value greater than or equal to  $M/2$  and less than  $M$ .

Claim 4 (Cancelled):

Docket No. 020417

Serial No. 10/765,766

Claim 5 (Cancelled).

6 (Currently Amended): ~~The circuit of claim 4~~ A programmable clock circuit to generate frequencies from an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal, the circuit comprising:

a counter configured to receive the input clock signal and to generate a counter signal having a frequency of M cycles for every N cycles of the input clock signal;

a comparator circuit coupled to the counter to compare a count value of the counter with predetermined count values and to generate comparator signals related to the comparison; and

a control circuit to generate an output clock signal based on the comparator signals to thereby select a rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and to select a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal;

wherein the counter is a M/N:D counter where D is related to a duty cycle of the output clock signal;

wherein the control circuit generates the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock signal if the comparator signals indicate that the counter has a value greater than or equal to  $D+M/2$  and less than  $D+M$ .

7 (Currently Amended): ~~The circuit of claim 4~~ claim 1 wherein the control circuit generates the output clock signal with 50% duty cycle.

8 (Currently Amended): ~~The circuit of claim 4~~ claim 1 wherein D is programmed with a  $1/2$  integer resolution.

Docket No. 020417

Serial No. 10/765,766

9 (Currently Amended): ~~The circuit of claim 1, further comprising~~ A programmable clock circuit to generate frequencies from an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal, the circuit comprising:

a counter configured to receive the input clock signal and to generate a counter signal having a frequency of M cycles for every N cycles of the input clock signal;

a comparator circuit coupled to the counter to compare a count value of the counter with predetermined count values and to generate comparator signals related to the comparison;

a control circuit to generate an output clock signal based on the comparator signals to thereby select a rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and to select a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal; and

a mode control input to override the control circuit wherein the control circuit generates the output clock signal with a rising edge and a falling edge of the output clock signal based on a rising edge of the input clock signal irrespective of the comparator signals.

Claim 10 (Cancelled).

11 (Currently Amended): ~~The circuit of claim 10, further comprising~~ A programmable clock circuit to generate frequencies from an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal, the circuit comprising:

a counter configured to receive the input clock signal and to generate a counter signal having a frequency of M cycles for every N cycles of the input clock signal;

a comparator circuit coupled to the counter to compare a count value of the counter with predetermined count values and to generate comparator signals related to the comparison; and

a control circuit to generate an output clock signal based on the comparator signals to thereby select a rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and to select a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal;

Docket No. 020417

Serial No. 10/765,766

wherein the comparator circuit comprises first, second and third comparators, the first comparator comparing the counter value with a value of  $M$  and  $M/2$ , the second comparator comparing the counter value with a value  $D$ , where  $D$  is a programmable value related to a duty cycle of the output signal, and the third comparator comparing the counter value with a value of  $D+M$  and  $D+M/2$ ; and

an adder to add a value of minus  $D$  to the counter value wherein the second comparator compares the counter value minus  $D$  to 0 and the third comparator compares the counter value minus  $D$  with a value of  $M$  and  $M/2$ .

12 (Original): The circuit of claim 1 wherein the control circuit comprises first and second synchronization latches wherein the first synchronization latch generates the output signal rising edge based on a rising edge of a selected input clock cycle if activated, the second synchronization latch generates a signal to generate the output signal rising edge based on a falling edge of an input clock cycle preceding the selected input clock cycle if activated.

13 (Original): The circuit of claim 1 wherein the control circuit comprises first and second synchronization latches wherein the first synchronization latch generates the output signal falling edge based on a rising edge of a selected input clock cycle if activated, the second synchronization latch generates a signal to generate the output signal falling edge based on a falling edge of an input clock cycle preceding the selected input clock cycle if activated.

14 (Currently Amended): A programmable clock circuit comprising:  
an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal; and  
a control circuit to generate an output clock signal having a frequency of  $M$  cycles for every  $N$  cycles of the input clock signal and to select a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and to select a falling edge of selected cycles of the output clock signal based on a rising edge of

Docket No. 020417

Serial No. 10/765,766

the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

a storage area containing data indicating which of the M cycles of the output clock signal having a rising edge based on a rising edge of the input clock and which of the M cycles of the output clock signal having a rising edge based on a falling edge of the input clock, the control circuit using the storage area data to generate the output clock signal.

15 (Original): The circuit of claim 14 wherein the control circuit is a state machine that generates selected cycles of the output clock signal with a rising edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock.

16 (Original): The circuit of claim 14 wherein the control circuit is a state machine that generates selected cycles of the output clock signal with a falling edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock.

Claim 17 (Cancelled).

18 (Currently Amended): ~~The circuit of claim 14, further comprising~~ A programmable clock circuit comprising:

an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

a control circuit to generate an output clock signal having a frequency of M cycles for every N cycles of the input clock signal and to select a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and to select a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

a storage area containing data indicating which of the M cycles of the output clock signal having a falling edge based on a rising edge of the input clock and which of the M

Docket No. 020417

Serial No. 10/765,766

cycles of the output clock signal having a falling edge based on a falling edge of the input clock, the control circuit using the storage area data to generate the output clock signal.

19 (Currently Amended): A programmable clock circuit comprising:

means for receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal; and

control means for generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal and for selecting a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and for selecting a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal;

wherein the control means comprises counter means for generating a counter value based on the input clock signal and comparison means for comparing the counter value to predetermined count values and output control means for generating the output clock signal with the rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal based on the comparing by the comparison means;

wherein the counter means comprises a M/N:D counter where D is related to a duty cycle of the output clock signal;

wherein the control means generates the output clock signal with a falling edge of the output clock signal based on a rising edge of the input clock signal if the comparator means indicates that the counter value is greater than or equal to D and less than D+M/2.

Claim 20 (Cancelled).

21 (Currently Amended): The circuit of ~~claim 20~~ claim 19 wherein the control means generates the output clock signal with a rising edge of the output clock signal based on a rising edge of the input clock signal if the comparator means indicates that the counter value is greater than or equal to zero and less than M/2.

Docket No. 020417

Serial No. 10/765,766

22 (Currently Amended): The circuit of ~~claim 20~~ claim 19 wherein the control means generates the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock signal if the comparator means indicates that the counter value is greater than or equal to  $M/2$  and less than  $M$ .

Claim 23 (Cancelled).

Claim 24 (Cancelled).

25 (Currently Amended): ~~The circuit of claim 23~~ A programmable clock circuit comprising:

means for receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal; and

control means for generating an output clock signal having a frequency of  $M$  cycles for every  $N$  cycles of the input clock signal and for selecting a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and for selecting a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal;

wherein the control means comprises counter means for generating a counter value based on the input clock signal and comparison means for comparing the counter value to predetermined count values and output control means for generating the output clock signal with the rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal based on the comparing by the comparison means;

wherein the counter means comprises a  $M/N:D$  counter where  $D$  is related to a duty cycle of the output clock signal;

Docket No. 020417

Serial No. 10/765,766

wherein the control means generates the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock signal if the comparator means indicates that the counter value is greater than or equal to  $D+M/2$  and less than  $D+M$ .

26 (Original): The circuit of claim 19 wherein the control means comprises a state machine that generates selected cycles of the output clock signal with a rising edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock.

27 (Original): The circuit of claim 19 wherein the control means comprises a state machine that generates selected cycles of the output clock signal with a falling edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock.

28 (Currently Amended): ~~The circuit of claim 19, further comprising A~~  
programmable clock circuit comprising:

means for receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

control means for generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal and for selecting a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and for selecting a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

storage means for storing data indicating which of the M cycles of the output clock signal having a rising edge based on a rising edge of the input clock and which of the M cycles of the output clock signal having a rising edge based on a falling edge of the input clock, the control means using the stored data to generate the output clock signal.



Docket No. 020417

Serial No. 10/765,766

29 (Currently Amended): ~~The circuit of claim 19, further comprising~~ A programmable clock circuit comprising:

means for receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

control means for generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal and for selecting a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and for selecting a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

storage means for storing data indicating which of the M cycles of the output clock signal having a falling edge based on a rising edge of the input clock and which of the M cycles of the output clock signal having a falling edge based on a falling edge of the input clock, the control means using the stored data to generate the output clock signal.

30 (Currently Amended): ~~The circuit of claim 19, further comprising~~ A programmable clock circuit comprising:

means for receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

control means for generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal and for selecting a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal and for selecting a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

Docket No. 020417

Serial No. 10/765,766

mode control means for overriding the control means wherein the control means always generates the output clock signal with a rising edge and a falling edge of the output clock signal based on a rising edge of the input clock signal.

31 (Currently Amended): A method for generating programmable clock frequencies comprising:

receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal; and

generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal with a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal, and a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal;

wherein generating the output clock signal comprises:

generating a counter value based on the input clock signal;

comparing the counter value to predetermined count values; and

generating the output clock signal with the rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and with a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal based on the comparing;

wherein the counting uses a M/N:D counter where D is related to a duty cycle of the output clock signal;

wherein the output clock signal is generated with a falling edge of the output clock signal based on a rising edge of the input clock signal if the comparing indicates that the counter value is greater than or equal to D and less than D+M/2.

Claim 32 (Cancelled).

33 (Currently Amended): The method of ~~claim 32~~ claim 31 wherein the output clock signal is generated with a rising edge of the output clock signal based on a rising edge of the

Docket No. 020417

Serial No. 10/765,766

input clock signal if the comparing indicates that the counter value is greater than or equal to zero and less than  $M/2$ .

34 (Currently Amended): The method of ~~claim 32~~ claim 31 wherein the output clock signal is generated with a rising edge of the output clock signal based on a falling edge of the input clock signal if the comparing indicates that the counter value is greater than or equal to  $M/2$  and less than  $M$ .

Claim 35 (Cancelled)

Claim 36 (Cancelled).

37 (Currently Amended): ~~The method of claim 35~~ A method for generating programmable clock frequencies comprising:

receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal; and

generating an output clock signal having a frequency of  $M$  cycles for every  $N$  cycles of the input clock signal with a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal, and a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal;

wherein generating the output clock signal comprises:

generating a counter value based on the input clock signal;

comparing the counter value to predetermined count values; and

generating the output clock signal with the rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and with a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal based on the comparing;

wherein the counting uses a  $M/N:D$  counter where  $D$  is related to a duty cycle of the output clock signal;

Docket No. 020417

Serial No. 10/765,766

wherein the output clock signal is generated with a falling edge of the output clock signal based on a falling edge of the input clock signal if the comparing indicates that the counter value is greater than or equal to  $D+M/2$  and less than  $D+M$ .

38 (Original): The method of claim 31 wherein generating the output clock signal comprises using a state machine that generates selected cycles of the output clock signal with a rising edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock.

39 (Original): The method of claim 31 wherein generating the output clock signal comprises using a state machine that generates selected cycles of the output clock signal with a falling edge of the output clock signal based on a rising edge of the input clock and selected cycles of the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock.

40 (Currently Amended): ~~The method of claim 31, further comprising~~ A method for generating programmable clock frequencies comprising:

receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal with a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal, and a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

storing data indicating which of the M cycles of the output clock signal having a rising edge based on a rising edge of the input clock and which of the M cycles of the output clock signal having a rising edge based on a falling edge of the input clock, the generating the output clock signal using the stored data to generate the output clock signal.

Docket No. 020417

Serial No. 10/765,766

41 (Currently Amended): ~~The method of claim 31, further comprising~~ A method for generating programmable clock frequencies comprising:

receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal with a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal, and a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

storing data indicating which of the M cycles of the output clock signal having a falling edge based on a rising edge of the input clock and which of the M cycles of the output clock signal having a falling edge based on a falling edge of the input clock, the generating the output clock signal using the stored data to generate the output clock signal.

42 (Currently Amended): ~~The method of claim 31, further comprising~~ A method for generating programmable clock frequencies comprising:

receiving an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal;

generating an output clock signal having a frequency of M cycles for every N cycles of the input clock signal with a rising edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal, and a falling edge of selected cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of other selected cycles of the output clock signal based on a falling edge of the input clock signal; and

generating a mode control signal to override the generating the output clock signal wherein generating the output clock signal always generates the output clock signal with a rising edge and a falling edge of the output clock signal based on a rising edge of the input clock signal.

Docket No. 020417

Serial No. 10/765,766

43 (Currently Amended): ~~The circuit of claim 1,~~ A programmable clock circuit to generate frequencies from an input clock signal having a predetermined frequency and having a rising edge and a falling edge associated with each clock cycle of the input clock signal, the circuit comprising:

a counter configured to receive the input clock signal and to generate a counter signal having a frequency of M cycles for every N cycles of the input clock signal;

a comparator circuit coupled to the counter to compare a count value of the counter with predetermined count values and to generate comparator signals related to the comparison; and

a control circuit to generate an output clock signal based on the comparator signals to thereby select a rising edge of the output clock signal based on a rising edge or a falling edge of the input clock signal and to select a falling edge of the output clock signal based on a rising edge or a falling edge of the input clock signal;

wherein the control circuit is configured to select a rising edge of some cycles of the output clock signal based on a rising edge of the input clock signal, and a rising edge of some other cycles of the output clock signal based on a falling edge of the input clock signal, and to select a falling edge of some cycles of the output clock signal based on a rising edge of the input clock signal, and a falling edge of some other cycles of the output clock signal based on a falling edge of the input clock signal.

44 (Previously Presented): The circuit of claim 1, wherein the control circuit is configured to generate selected cycles of the output clock signal with a rising edge based on a rising edge of the input clock signal, and selected cycles of the output clock signal with a rising edge of the output clock signal based on a falling edge of the input clock.

45 (Previously Presented): The circuit of claim 44, wherein the control circuit is configured to generate selected cycles of the output clock signal with a falling edge based on a rising edge of the input clock signal, and selected cycles of the output clock signal with a falling edge of the output clock signal based on a falling edge of the input clock.